

GERHAD IR Dome Camera

Model : GH-2600IR-HS

FEATURES :

- 520 TV Line
- 4mm Lens
- 1/3" Sony and Sharp CCD Sensor



SPECIFICATION

Image Device	1/3" Sony & Sharp CCD sensor
Scanning Frequency	NTSC:15,734KHz(H), 60Hz(V);PAL: 15,625KHz(H),50Hz(V)
Scanning System	NTSC: 525 line 2:1 interlace PAL:625 lines 2:1 interlace
Effective Pixels	NTSC: 512(H) x 492(V); PAL:512(H) x 582(V)
Electronic Shutter	N:1/60- 1/100,000sec (Auto);P:1/50-1/100,000sec (Auto)
Horizontal	420/520 TV lines
White-balance	Auto white balance (2500°K~9500°k)
Synchronizing System	Internal
Sensitivity	0.2 Lux , 0 Lux at IR on / F2.0
BLC	Auto
Signal to Noise	More than 48dB (AGC off)
IR Distance	15 Meters (Based on: object of view reflected IR light)
IR LED	High Light LED x 20 pcs
IR Status	500
IR View Angle	View angle: 70°, Beam spread: 40°/per LED
IR Wavelength	850nm ± 25nm
LED Life	More than 10,000 hours
Lens	4 mm Standard (4,8,12,16mm option)
Power Consumption	IR on: 180mA, IR off: 120mA (DC 12V) ± 5mA
Power Supply	DC 12V, AC 90V ~ 260V (Auto)
Temperature	Operating: -10 to 50°C
Video Output	Composite 1.0 Vp-p at 75 ohm
Construction	Aluminum with sunshield weatherproof
Dimensions	115(W) x 75(H)
Weight	0.150kg