

IP DOME CAMERA

VS-1NAD

Features

- Support video out
- 2M-Pixel CMOS Sensor
- Power over Ethernet available
- 3-Axis Adjustments
- IR LED Built in 12M available
- H.264/ JPEG/ MPEG4 compression
- SD card backup
- 2-way audio
- Powerful mobile surveillance function, support 3GPP, JAVA, iPhone & Windows mobile.
- SDK for Software Integration
- Free Bundle 36 ch recording software



H.264 CMOS 2 Mega-Pixel IP Dome Camera

Specifications



Hardware	
CPU	ARM 9 ,32 bit RISC
RAM	128MB
Flash	8MB
Image Sensor	1/3" CMOS(2M-Pixel)
Support DC IRIS	Yes
Lens Type	Vari-focal 2.7~9mm Mega Pixel Lens
ICR	Mechanism IR cut Filter(Optional)
LED	Built-in 18 IR LED (optional) IR Distance-12M (Optional)
Alarm I/O	1 in/ 1 Relay Out
Video Out	x1
Audio In	x1
Audio Out	x1
Power over Ethernet	Yes
Power Consumption	DC 12V 480mA (with IR)
Dimensions	132mm (φ) * 108.4mm (H)
Client system requirements	
OS	Windows 2000, XP, 2003, Microsoft IE 6.0 or above
Hardware	
Suggested	Intel Dual Core 1.66G, RAM: 1024MB, Graphic card: 128MB
Minimum	Intel-C 2.8G, RAM: 512MB, Graphic card: 64MB

Network	
Ethernet	10/ 100 Base-T
Network Protocol	HTTP, TCP/ IP, SMTP, FTP, PPPoE, DHCP, DDNS, NTP, UPnP, 3GPP
System	
Video Resolution	1600x1200, 1280x1024, 1280x960, 1280x720, 800x600, 640x480, 320x240, 176x144
Video Adjust	Brightness, Contrast, Sharpness, BLC, Night Mode
Triple Streaming	Yes
Image Snapshot	Yes
Full Screen Monitoring	Yes
Privacy Mask	Yes, 3 different areas
Compression Format	H.264/ JPEG/ MPEG4 (3GPP only)
Video Bitrates Adjust	CBR, VBR
Motion Detection	Yes, 3 different areas
Triggered Action	Mail, FTP, Save to SD card, Relay
Pre/ Post Alarm	Yes, configurable
Security	Password protection
Firmware Upgrade	HTTP mode, can be upgraded remotely
Simultaneous Connection	Up to 10
Audio	Yes, 2-way
SD card management	
Recording Trigger	Motion Detection, IP check, Network break down (wire only), schedule, relay
Video Format	AVI, JPEG
Video Playback	Yes
Delete Files	Yes